

163 [tech brochure01121](#)

Radiant Mixing Block

hermostatic mixing unit with insulation. Compatible with 55 Hydro ink series. Includes rundfos three seed pump. Ad ustable differential pressure by-pass valve. emperature gages. Shutoff ball valves. 1 NP female union inlet fittings. By-pass ad ustable from 2 to 10 psi. Max working pressure: 1 5 psi. Setting temperature range: 0-150°F. Power supply: 120 V - 50 0 H .



Code	Description	Pk	Lbs
163600A	1" NPT outlet for right side flow	1	21.0
163610A	1" NPT outlet for left side flow	1	21.0

163 [tech brochure01121](#)

Radiant Mixing Block

hermostatic mixing unit. Compatible with 55 Hydro ink series. Includes rundfos three seed pump. 1 NP female union inlet fittings. Max working pressure: 1 5 psi. Setting temperature range: 0-150°F. Power supply: 120 V - 50 0 H .



Code	Description	Pk	Lbs
163640A	1" NPT outlet for right side flow	1	16.0
163650A	1" NPT outlet for left side flow	1	16.0
163649A	1" Sweat outlet for right side flow	1	16.0
163659A	1" Sweat outlet for left side flow	1	16.0

163 [tech brochure01121](#)

Thermostatic mixing unit. Compatible with 559 Hydro ink series. Max working pressure: 1 5 psi. Setting temperature range: 0-150°F.



Code	Description	Pk	Lbs
163001	1" NPT inlet x 1-1/4" union nut outlet	1	8.0

Diagram with 559 series HydroLink

