

## 553

tech brochure 01061

### AutoFill



Pre-adjustable automatic filling unit, anti-scale, visual system pressure setting indicator. Complete with manual shutoff valve, strainer and check valve.  
 Max. inlet pressure: 230 psi.  
 Max. working temperature: 150°F.  
 Setting pressure range: 3 - 60 psi.  
 Preset outlet pressure: 15 psi.

Code	Description	Pk	Lbs
553542A	1/2" NPT inlet x 1/2" NPT outlet	10	17.4
553549A	1/2" sweat inlet x 1/2" NPT outlet	10	17.4

## 573

tech brochure 01061

Dual check continuous pressure backflow preventer with atmospheric vent. Female union connections.  
 Max. working pressure: 175 psi.  
 Working temperature range: 32 - 210°F.  
 ASSE 1012 listed and CSA B64.3 certified



Code	Description	Pk	Lbs
573403A	1/2" NPT	20	33.5
573409A	1/2" sweat	20	33.5
573493A	1/2" NPT + 1/2" sweat	20	33.5
573503A	3/4" NPT	20	33.5

## 573

tech brochure 01061

### AutoFill Combo

Pre-adjustable automatic filling unit with backflow preventer.

Max. inlet pressure: 175 psi.  
 Max. working temperature: 150°F.  
 Setting pressure range: 3 - 60 psi.  
 Preset outlet pressure: 15 psi.



Code	Description	Pk	Lbs
573002A	1/2" NPT inlet + 1/2" NPT outlet	1	5.0
573009A	1/2" sweat inlet + 1/2" NPT outlet	1	5.0

## 510

Check valve to prevent natural circulation of water. Straight through or angled connection. Manual release knob.

Max. working pressure: 150 psi.  
 Max. working temperature: 250°F.



Code	Description	Pk	Lbs
510502A	3/4" NPT	10	9.8

## 519

Differential pressure by-pass valve with threaded inlet and threaded or sweat union outlet.

Adjustable from 2 to 10 psi.  
 Max. working pressure: 150 psi.  
 Max. working temperature: 230°F.  
 · 3/4" flow up to 9 gpm.  
 · 1" flow up to 40 gpm.  
 · 1-1/4" flow up to 45 gpm.



Code	Description	Pk	Lbs
519502A	3/4" NPT + 3/4" NPT outlet	10	9.8
519600A	1" NPT + 1" NPT outlet	1	1.4
519609A	1" NPT + 1" sweat outlet	1	1.4
519700A	1-1/4" NPT + 1-1/4" NPT outlet	1	1.5
519709A	1-1/4" NPT + 1-1/4" sweat outlet	1	1.5

## 626

Flow switch for heating and air conditioning systems.

Suitable for 1" to 8" pipe size.  
 Working pressure: 150 psi.  
 Working temperature: 250°F.  
 UL Listed



Code	Description	Pk	Lbs
626600A	1" NPT male thread	1	2.3